

# Product data sheet

Specifications



## communication module Profibus DP V1, Altivar, 12Mbps, 1 female SUB D9 connector

VW3A3607

**Product availability: Stock - Normally stocked in distribution facility**

**Price\*: 281.36 USD**

### Main

Range of Product	Altivar
Product or Component Type	Communication module
accessory / separate part category	Communication accessories

### Complementary

Product Compatibility	Lexium 32M
Range compatibility	Altivar 32 Altivar Machine ATV340 except Sercos drives Altivar Easy 610 Lexium 32 Altivar Process ATV900 Altivar Process ATV600 Altivar Machine ATV320 Altivar Process Modular
Communication Port Protocol	Profibus DP V1
Electrical connection	1 female connector SUB-D 9
Transmission Rate	9.6 kbps...12 Mbps
Addressing	1...126 configurable by graphic terminal/SoMove software Configuration settings
Communication service	4 configurable telegrams Mapping of the process data from the master Parameters management compliant with PROFIdrive V4.1 Several DP V1 messaging modes Drive profile native ATV32 IEC 61800-7-201 (CiA 402)
Display type	1 LED RUN 1 LED bus fault (BF)
diagnostic function	Diagnostic data with VSD status Host drive handled from two masters (MS0 and MS1) Standard identification and maintenance requests
Bus profile	PROFIdrive CiA 402

### Environment

Standards	IEC 61800-7-201 (CiA 402)
-----------	---------------------------

### Ordering and shipping details

Category	US1PC5118263
Discount Schedule	PC51

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>GTIN</b>	3606480177583
<b>Returnability</b>	Yes
<b>Country of origin</b>	FR

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	1.850 in (4.700 cm)
<b>Package 1 Width</b>	2.402 in (6.100 cm)
<b>Package 1 Length</b>	3.543 in (9.000 cm)
<b>Package 1 Weight</b>	2.152 oz (61.000 g)
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	100
<b>Package 2 Height</b>	11.811 in (30.000 cm)
<b>Package 2 Width</b>	11.811 in (30.000 cm)
<b>Package 2 Length</b>	15.748 in (40.000 cm)
<b>Package 2 Weight</b>	14.645 lb(US) (6.643 kg)

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

Pvc Free

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations

California Proposition 65 **WARNING:** This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Image of product / Alternate images

Alternative

---





