


## CHARACTERISTICS

Ambient temperature	-10 ÷ +70 °C	
Fluid	filtered air 50 µm, with or without lubrication	
Commutation system	poppet	
Max pressure	10 bar	
Connections	G1/8	G1/4
Nominal bore (mm)	2,3	8
Nominal flow rate (NL/min)	98	800
<b>PNEUMATIC FOOT VALVE:</b>		
Valve body	zamak	
Foot valve lever	aluminium	
Pedal body and protection	plastic material with reinforcing steel plate	
Seals	oil and wear resistant compound	
Spool	aluminium	
<b>SOLENOID FOOT VALVE</b>		
Valve body, foot valve lever, protection	dielectric plastic material	




Available ATEX version upon request

CE Ex II 2Gc IIC T5 II 2Dc T100°C


## Pneumatic foot valve G1/4 with protection




### Spring return



### Bistable



### With safety control



### External operation - Spring return



### External operation - bistable




### External operation with safety control




## Pneumatic foot valve G1/4 without protection



### Spring return




### Bistable



## Pneumatic foot valve G1/8 with protection



### Spring return



## Solenoid foot valve

- AM-5050  
No electrical microswitch
- AM-5051  
Electrical microswitch
- AM-5052  
Double electrical microswitch

Version without protection available upon request

See ATEX Catalogue for types and versions